```
   Help
#include  "bs1d_doublim.h"

static int Psor_Out(double s,NumFunc_1  *L,
    NumFunc_1  *U,NumFunc_1  *Rebate,NumFunc_1  *p,double
    t,double r,double divid,double sigma,int N,int M,
    double theta,double omega,double epsilon,double *ptpr
    ice,double *ptdelta)
{
  int      Index,PriceIndex,TimeIndex;
  int      j,loops;
  double   k,vv,h,z,alpha,beta,gamma,y,alpha1,bet
    a1,gamma1,down,upwind_alphacoef;
  double   error,norm,x,up,rebate,l,u,pricenh,pr
    icen2h,priceph;
  double   *P,*Obst,*Rhs;

  /*Memory Allocation*/
  P=(double *)malloc((N+2)*sizeof(double));
  if (P==NULL)
    return MEMORY_ALLOCATION_FAILURE;
  Obst=(double *)malloc((N+2)*sizeof(double));
  if (Obst==NULL)
    return MEMORY_ALLOCATION_FAILURE;
  Rhs=(double *)malloc((N+2)*sizeof(double));
  if (Rhs==NULL)
    return MEMORY_ALLOCATION_FAILURE;

  /*Time Step*/
  k=t/(double)M;

  /*Space Step*/
  u=(U->Compute)(U->Par,0);
  l=(L->Compute)(L->Par,0);
  rebate=(Rebate->Compute)(Rebate->Par,0);
  x=log(s);
  down=log(l);
  up=log(u);
  h=(up-down)/(double)(N+1);

  /*Coefficient of diffusion augmented*/
```

```
vv=0.5*sigma*sigma;
z=(r-divid)-vv;
if ((h*fabs(z))<=vv)
  upwind_alphacoef=0.5;
else {
  if (z>0.) upwind_alphacoef=0.0;
  else if (z<=0.) upwind_alphacoef=1.0;
}
vv-=z*h*(upwind_alphacoef-0.5);

/*Lhs factor of theta-schema*/
alpha=theta*k*(-vv/(h*h)+z/(2.0*h));
beta=1.0+k*theta*(r+2.*vv/(h*h));
gamma=k*theta*(-vv/(h*h)-z/(2.0*h));

/*Rhs factor of theta-schema*/
alpha1=k*(1.0-theta)*(vv/(h*h)-z/(2.0*h));
beta1=1.0-k*(1.0-theta)*(r+2.*vv/(h*h));
gamma1=k*(1.0-theta)*(vv/(h*h)+z/(2.0*h));

/*Terminal Values*/
for(PriceIndex=1;PriceIndex<=N;PriceIndex++) {
  Obst[PriceIndex]=(p->Compute)(p->Par,exp(dow
  n+(double)PriceIndex*h));
  P[PriceIndex]=Obst[PriceIndex];
}
P[0]=rebate;
P[N+1]=rebate;

/*Finite Difference Cycle*/
for(TimeIndex=1;TimeIndex<=M;TimeIndex++)
  {
    /*Init Rhs*/
    for(j=1;j<=N;j++)
      Rhs[j]=P[j]*beta1+alpha1*P[j-1]+gamma1*P[
  j+1];

    /*Psor Cycle*/
    loops=0;
    do
      {
```

```
          error=0.;
          norm=0.;

          for(j=1;j<=N;j++)
            {
              y=(Rhs[j]-alpha*P[j-1]-gamma*P[j+1]
  )/beta;
              y=MAX(Obst[j],P[j]+omega*(y-P[j]));

              error+=(double)(j+1)*fabs(y-P[j]);
              norm+=fabs(y);
              P[j]=y;
            }

          if (norm<1.0) norm=1.0;
          error=error/norm;

          loops++;
        }
    while ((error>epsilon) && (loops<MAXLOOPS))
  ;
  }
Index=(int)floor((x-down)/h);

/*Price*/
if ((x==up)&&(x==down))
  *ptprice=P[0];
else
  *ptprice=P[Index]+(P[Index+1]-P[Index])*(exp(
  x)-exp(down+Index*h))/(exp(down+(Index+1)*h)-exp
  (down+Index*h));

/*Delta*/
if ((x==up)&&(x==down))
  *ptdelta=0.0;
else {
  pricenh=P[Index+1]+(P[Index+2]-P[Index+1])*(
  exp(x+h)-exp(down+(Index+1)*h))/(exp(down+(Index+2
  )*h)-exp(down+(Index+1)*h));
  if (Index>0) {
    priceph=P[Index-1]+(P[Index]-P[Index-1])*(
```

```
    exp(x-h)-exp(down+(Index-1)*h))/(exp(down+(Index)*
    h)-exp(down+(Index-1)*h));
      *ptdelta=(pricenh-priceph)/(2*s*h);
    } else {
      pricen2h=P[Index+2]+(P[Index+3]-P[Index+2])
    *(exp(x+2*h)-exp(down+(Index+2)*h))/(exp(down+(
    Index+3)*h)-exp(down+(Index+2)*h));
      *ptdelta=(4*pricenh-pricen2h-3*(*ptprice))/
    (2*s*h);
    }
  }

  /*Memory Desallocation*/
  free(P);
  free(Obst);
  free(Rhs);

  return OK;
}

int CALC(FD_Psor_Out)(void *Opt,void *Mod,Pricing
    Method *Met)
{
  TYPEOPT* ptOpt=(TYPEOPT*)Opt;
  TYPEMOD* ptMod=(TYPEMOD*)Mod;
  double r,divid;

  r=log(1.+ptMod->R.Val.V_DOUBLE/100.);
  divid=log(1.+ptMod->Divid.Val.V_DOUBLE/100.);

  return Psor_Out(ptMod->S0.Val.V_PDOUBLE,ptOpt->
    LowerLimit.Val.V_NUMFUNC_1,ptOpt->UpperLimit.Val.
    V_NUMFUNC_1,ptOpt->Rebate.Val.V_NUMFUNC_1,ptOpt->
    PayOff.Val.V_NUMFUNC_1,
                  ptOpt->Maturity.Val.V_DATE-pt
    Mod->T.Val.V_DATE,r,divid,ptMod->Sigma.Val.V_PDOU
    BLE,
                  Met->Par[0].Val.V_INT,Met->Par[
    1].Val.V_INT, Met->Par[2].Val.V_RGDOUBLE,Met->
    Par[3].Val.V_RGDOUBLE,Met->Par[4].Val.V_RGDOUBLE,
                  &(Met->Res[0].Val.V_DOUBLE),&(
```

```
    Met->Res[1].Val.V_DOUBLE));
}

int CHK_OPT(FD_Psor_Out)(void *Opt, void *Mod)
{
  Option* ptOpt=(Option*)Opt;
  TYPEOPT* opt=(TYPEOPT*)(ptOpt->TypeOpt);

  if ((opt->Parisian).Val.V_BOOL==WRONG)
  if ( (strcmp( ((Option*)Opt)->Name,"
    DoubleCallOutAmer")==0) || (strcmp( ((Option*)Opt)->Name,"
    DoublePutOutAmer")==0) )
    return OK;
  return WRONG;
}

static int MET(Init)(PricingMethod *Met)
{
  static int first=1;

  if (first)
    {
      Met->Par[0].Val.V_INT2=100;
      Met->Par[1].Val.V_INT2=100;
      Met->Par[2].Val.V_RGDOUBLE=0.5;
      Met->Par[3].Val.V_RGDOUBLE=1.5;
      Met->Par[4].Val.V_RGDOUBLE=1.0e-7;

      first=0;
    }

  return OK;
}

PricingMethod MET(FD_Psor_Out)=
{
  "FD_Psor_Out",
  {{"SpaceStepNumber",INT2,100,ALLOW    },{"TimeS
    tepNumber",INT2,100,ALLOW},
   {"Theta",RGDOUBLE051,100,ALLOW},{"Omega",RG
    DOUBLE12,100,ALLOW}, {"Epsilon",RGDOUBLE,100,ALLOW},{"
```

```
    ",END,0,FORBID}},
  CALC(FD_Psor_Out),
  {{"Price",DOUBLE,100,FORBID},{"Delta",DOUBLE,10
    0,FORBID} ,{" ",END,0,FORBID}},
  CHK_OPT(FD_Psor_Out),
  CHK_psor,
  MET(Init)
};
```

References